

RINGO C S-I-Z

Spotlight - Adjustable



Quick info

GENERAL

General light
with internal LED driver

LED

COB LED module
2700K, 3000K, 4000K
CRI>90
Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination
Beam angle 20°-35°

PHYSICAL

Aluminium
Powder coating

Function

RINGO seamlessly blends functionality with refined aesthetics. Its elegant design features an internal LED driver and an optimised passive cooling system, which work together to maintain low operating temperatures and ensure a long LED lifespan.

The adjustable head offers flexible positioning, with 355° rotation and 90° pivot capabilities. Additionally, the front ring enhances glare control, while the adaptable lens ensures high luminous efficiency and uniform light distribution, delivering exceptional visual comfort.


Features

Concise structure with driver inside housing



High quality optical lens ensures precise lighting distribution

Dimensions



RINGO C S-I-Z

Spotlight - Adjustable

Ordering info

SYSTEM POWER

11W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI>90

ELECTRICAL

Non-Dim
Phase-Dim
1-10V Dim
DALI

HOUSING

White
Black

LENS



20°-35° Beam

ACCESSORIES



Honeycomb Mesh

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	Beam
RINGO C S-I-Z-11W-930	900lm	9W	11W	90	20°- 35°
RINGO C S-I-Z-11W-940	950lm	9W	11W	90	20°- 35°

Ordering Information

RINGO C S-I-Z - XXW - XX - XX - XX - ND - XX

Wattage	CRI	CCT	Accessories	Controls	Finish
(11) 11W	(27) 2700K (30) 3000K (40) 4000K	(90) CRI>90	() No Accessory (HM) Honeycomb	(ND) Non-Dim (PH) Phase-Dim (1-10) 1-10V (DA) DALI	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.