




Key Features

- L70 B50. CRI≥80.
- Rated 50,000 hours.
- Multi-watt and multi-colour temprature selectable.
- High efficiency SMD LED chips.
- High impact polycarbonate body.
- Stainless steel clips and screws.
- High impact polycarbonate diffuser.
- Optional integrated microwave sensor with switchable or remote settings.
- Optional integrated emergency system.
- Surface or suspended mounting options.

Dimensions



Technical Information

| Length | Colour Temp           | Wattage |        |        |        |        |        |        |        |
|--------|-----------------------|---------|--------|--------|--------|--------|--------|--------|--------|
|        |                       | 10W     | 14W    | 20W    | 24W    | 26W    | 30W    | 36W    | 40W**  |
| 06     | 3K                    | 930Lm   | 1300L  | 1860Lm |        |        |        |        |        |
|        | 4K / 5K / 5.7K / 6.5K | 1000Lm  | 1400Lm | 2000Lm |        |        |        |        |        |
| 12     | 3K                    | 960Lm   | 1302Lm | 1860Lm | 2232Lm | 2418Lm | 2790Lm | 3345Lm | 3720Lm |
|        | 4K / 5K / 5.7K / 6.5K | 1000Lm  | 1400Lm | 2000Lm | 2400Lm | 2600Lm | 3000Lm | 3600Lm | 4000Lm |

Code

ETW/12/ND

| Product Series |           | Wattage & Nominal Dimensions |        | Driver |                          |
|----------------|-----------|------------------------------|--------|--------|--------------------------|
| ETW            | Surface   | 06                           | 600mm  | ND     | Non Dim                  |
| ETW-SUS        | Suspended | 12                           | 1200mm | EM     | Emergency                |
|                |           |                              |        | MS     | Microwave Sensor         |
|                |           |                              |        | RC     | Remote control of sensor |

See Technical Information Table for configurations options.  
Specifications subject to change without notice.

