

ICU1X55 / ICU1X55-10D

Downlight



Quick info

GENERAL

Recessed

Fixed

LED

SMD LED module

3000K, 4000K

CRI>90

Bining < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination

Beam angle 10°, 18°, 24°, 36°, 50°

PHYSICAL

Aluminium

Powder coating

Function

Discover our ICU collection featuring a series of minimalist, functional, and versatile lighting solutions, designed to adapt seamlessly to both retail and residential environments.

Each fixture offers 350° rotation and 90° tilt for flexible lighting schemes and precise illumination.

Featuring a high-quality optical lens, this range supports spot, narrow, and medium beam angles to suit a variety of applications.

Features

Deliate light engine

High quality anti-glare ring


LED Engine can be removed separately

350° rotatable and 90° tilttable



Dimensions

K1X55/K1X55-10D



ICU1X55 / ICU1X55-10D

Downlight

Ordering info

SYSTEM POWER
11W
COLOUR TEMPERATURE
3000K
4000K
COLOUR RENDERING INDEX
CRI>90
HOUSING
White
Black

LENS



10° Beam15° Beam



24° Beam36° Beam



50° Beam

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	Beam
ICU1X55-9W-930	720lm	9W	11W	90	18°
ICU1X55-9W-940	800lm	9W	11W	90	18°
ICU1X55-9W-930	720lm	9W	11W	90	24°
ICU1X55-9W-940	800lm	9W	11W	90	24°
ICU1X55-9W-930	720lm	9W	11W	90	36°
ICU1X55-9W-940	800lm	9W	11W	90	36°
ICU1X55-9W-930	720lm	9W	11W	90	50°
ICU1X55-9W-940	800lm	9W	11W	90	50°
ICU1X55-9W-930-10D	720lm	9W	11W	90	10°
ICU1X55-9W-940-10D	800lm	9W	11W	90	10°

Ordering Information

ICU1X55 - XXW - XX - XX - XX - XX

Wattage

CRI

CCT

Lens

Finish

(9) 9W

(90) CRI>90

(30) 3000K
(40) 4000K

(10) 10°
(18) 18°
(24) 24°
(36) 36°
(50) 50°

(10) Black
(11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.