

CWP-LED


LED WEATHERPROOF



Key Features

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- Stainless steel toggle clip fixings.
- UV stabilized high impact polycarbonate diffuser.
- Tamper proof clips with self tapping screws available upon request.
- Stainless Steel spring fixing brackets for mounting onto surfaces.
- Suitable for suspension with the stainless steel triangle provided.
- Ambient temperature -25° to 45°.

Dimensions



Technical Information

Configurations	Non Dim System wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600
2x08W	22.20	2440	600 & 1200
4x08W	38.10	4880	1200
1x14W	17.62	2200	600
2x14W	34.34	4400	600 & 1200
4x14W	68.52	8800	1200

Code

CWP-LED/4X08/12/40/TS/ND

Product Series	# of boards	Wattage of boards	Nominal Length	Colour Temperature	Tamper Proof screws	Driver
CWP-LED	1 1 Board 2 2 Board 4 4 Board	8 8W 14 14W	06 600 12 1200	30 3000K 40 4000K	TS Tamper Proof Screws	ND Non Dim DALI DALI Dim SD Switch Dim ME Emergency

Specifications subject to change without notice.

