

# VEKTA V2525C



## Key Features


- 300mm minimum bend radius
- Even Illumination
- Clip on diffuser for easy installation
- Direct Illumination
- Typical length is 2.5m (longer lengths available on request)
- Other RAL colours available on request
- SELV LED Engine
- Complies with relevant Australian Standards

## Compliance



\*Cyanosis compliant on request

## Colour Options



Code

Example:

V2525C-S1090300DDO10-2400

Profile	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
V2525C	S - Surface Mount P - Pendant Wire D - Pendant Rod	10 - 9.6 W/m (486lm/m) 15 - 14.4 W/m (729lm/m) 20 - 19.2W/m (972lm/m) 28 - 28.8W/m (1457lm/m)	80 - CRI>80 90 - CRI>90	30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K RGB RGBW TW	OD - Opal	DO - Non-Dim DA - DALI-Dim SW - Switch-Dim CA - Casambi	10 - Black 11 - White 12 - Silver 13 - Gold Bronze CU - Custom	- XXXX mm

## Mounting

Surface Mounted (S) Wire Pendant (P)  
Rod Pendant (D)



## Dimensions

