

# FHL-LED


LED BATTEN



## Key Features

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Squareline batten range fabricated from 0.7mm zincseal steel with powder coated white finish.
- Wide body or narrow body available.
- Available in 1.0mm aluminium body for marine/corrosive environment (FHLAL-LED).
- Suitable for fixing directly to ceiling or may be suspended with chains or rods.

## Dimensions



## Technical Information

Configuration	Non Dim System Wattage	Combined board output (lm)	Dimensions
1x08W	10.6	1220	615/N
2x08W	22.20	2440	615/W & 1175/N
4x08W	38.10	4880	1175/W
1x14W	17.62	2200	615/N
2x14W	34.34	4400	615/W & 1175/N
4x14W	68.52	8800	1175/W

## Code

FHL-LED/2X08/12/N/40/ND

Product Series		# of Boards		Wattage (W)		Nominal Dimension		Fitting Width		CCT		Driver	
FHL-LED	Steel Body	1	1 Board	8	8 Watts	6	600mm	N	Narrow Body	30	3000K	ND	Non Dim
FHLAL-LED	Aluminium Body	2	2 Board	14	14 Watts	12	1200mm	W	Wide Body	40	4000K	DALI	DALI Dim
		4	4 Board									SD	Switch Dim

See Technical Information Table for configurations options  
Specifications subject to change without notice

