

iSTART 45

LED Downlight Adjustable



Quick info

GENERAL

Recessed

Adjustable

Fixed

Trimmed

Round

Square

LED

COB LED module

3000K, 4000K

CRI>90

Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination

Beam angle 18°, 24°, 35°, 55°

PHYSICAL

Aluminium

Powder coating

Function

iSTART 45 is a versatile series comprising of adjustable and fixed fittings available in trimmed or trimless.



iSTART streamlines the process with a single light engine, with an adjustable head that offers flexible positioning, with 355° rotation and 90° pivot capabilities.

A smart mechanical design ensures precise alignment.

Features



Dimensions



iSTART 45

LED Downlight Adjustable

Ordering info

SYSTEM POWER

6W

COLOUR TEMPERATURE

3000K
4000K

COLOUR RENDERING INDEX

CRI>90

ELECTRICAL

Non-Dim
Phase-Dim
1-10V Dim
DALI

HOUSING

White
Black

LENS



18° Beam



24° Beam



35° Beam



55° Beam

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	Beam
SRA45-4W-930	350lm	4W	6W	90	18°/24°/35°/55°
SRA45-4W-940	380lm	4W	6W	90	18°/24°/35°/55°
SSA45-4W-930	350lm	4W	6W	90	18°/24°/35°/55°
SSA45-4W-940	380lm	4W	6W	90	18°/24°/35°/55°

Ordering Information

XXX45 - XXW - XX - XX - XX - ND - XX

Fitting	Wattage	CRI	CCT	Lens	Controls	Finish
(SRA) Round Downlight (SSA) Square Downlight	(4) 4W	(30) 3000K (40) 4000K	(90) CRI>90	(18) 18° (24) 24° (35) 35° (55) 55°	(ND) Non-Dim (PH) Phase-Dim (1-10) 1-10V Dim (DA) DALI	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.