

RINGO K

Spotlight



Quick info

GENERAL

Track Light
with in-track LED driver

LED

COB LED module
2700K, 3000K, 4000K
CRI>80, CRI>90
Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination
Beam angle 20°, 35°, 55°

PHYSICAL

Aluminium
Powder coating

Function


RINGO seamlessly blends functionality with refined aesthetics. Its elegant design features an in-track LED driver and an optimised passive cooling system, which work together to maintain low operating temperatures and ensure a long LED lifespan.

The adjustable head offers flexible positioning, with 355° rotation and 90° pivot capabilities. Additionally, the front ring enhances glare control, while the adaptable lens ensures high luminous efficiency and uniform light distribution, delivering exceptional visual comfort.

Features



Dimensions



RINGO K Spotlight

Ordering info

SYSTEM POWER

28W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI>80
CRI>90

HOUSING

White
Black

LENS



20° Beam



35° Beam



55° Beam

ACCESSORIES



Honeycomb Mesh

TRACK ADAPTER



TRIDONIC
3-Circuit



OSRAM 3-Circuit

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	Beam
RINGO K-28W-930-20	2200lm	25W	28W	90	20°
RINGO K-28W-940-20	2400lm	25W	28W	90	20°
RINGO K-28W-930-35	2200lm	25W	28W	90	35°
RINGO K-28W-940-35	2400lm	25W	28W	90	35°
RINGO K-28W-930-55	2200lm	25W	28W	90	55°
RINGO K-28W-940-55	2400lm	25W	28W	90	55°

Ordering Information

RINGO K - XXW - XX - XX - XX - XX - ND - XX

Wattage	CRI	CCT	Lens	Accessories	Track Adaptor	Finish
(28) 28W	(27) 2700K (30) 3000K (40) 4000K	(80) CRI>80 (90) CRI>90	(20) 20° (35) 35° (55) 55°	() No Accessory (HM) Honeycomb	(ND) OSRAM 3-Circuit (DA) TRIDONIC 3-Circuit	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.