

RINGO M-E-Z

Spotlight



Quick info

GENERAL

Track Light
with in-track LED driver

LED

COB LED module
2700K, 3000K, 4000K
CRI>80, CRI>90
Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination
Beam angle 18°-35°

PHYSICAL

Aluminium
Powder coating

Function


RINGO seamlessly blends functionality with refined aesthetics. Its elegant design features an in-track LED driver and an optimised passive cooling system, which work together to maintain low operating temperatures and ensure a long LED lifespan.

The adjustable head offers flexible positioning, with 355° rotation and 90° pivot capabilities. Additionally, the front ring enhances glare control, while the adaptable lens ensures high luminous efficiency and uniform light distribution, delivering exceptional visual comfort.

Features



Dimensions



RINGO M-E-Z Spotlight

Ordering info

SYSTEM POWER

15W
21W

COLOUR TEMPERATURE

2700K
3000K
4000K

COLOUR RENDERING INDEX

CRI>80
CRI>90

HOUSING

White
Black

LENS



18°-35° Beam

ACCESSORIES



Honeycomb Mesh

TRACK ADAPTER



TRIDONIC
3-Circuit



OSRAM 3-Circuit

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	Beam
RINGO M-E-Z-15W-930	1300lm	13W	15W	90	18°-35°
RINGO M-E-Z-15W-940	1400lm	13W	15W	90	18°-35°
RINGO M-E-Z-21W-930	1700lm	18W	21W	90	18°-35°
RINGO M-E-Z-21W-940	1800lm	18W	21W	90	18°-35°

Ordering Information

RINGO M-E-Z - XXW - XX - XX - XX - ND - XX

Wattage	CRI	CCT	Accessories	Track Adaptor	Finish
(15) 15W (21) 21W	(27) 2700K (30) 3000K (40) 4000K	(80) CRI>80 (90) CRI>90	() No Accessory (HM) Honeycomb	(ND) OSRAM 3-Circuit (DA) TRIDONIC 3-Circuit	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.