



Key Features


- Minimum bend radius is 400mm
- Custom curved aluminium extruded profile
- Complies with relevant Australian standards
- SELV LED Engine
- Detailed shop drawings
- Plug and play wire looms
- Typical length is 2.5m (longer lengths available on request)

Compliance



*Cyanosis compliant on request

Colour Options



Code


Example:

V8040RC-R158030ODD010-2400

Profile	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
V8040RC	R - Recessed	15 - 14.4 W/m (1014lm/m) 20 - 19.2W/m (1352lm/m) 28 - 28.8W/m (2028lm/m) 43 - 43.2W/m (3042lm/m) 58 - 58.7W/m (4056lm/m)	80 - CRI>80 90 - CRI>90	30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K RGB3 - RGBW 3000K RGB4 - RGBW 4000K	OD - Opal	DO - Non-Dim DA - DALI-Dim SW - Switch-Dim CA - Casambi D4 - DALI RGBW C4 - Casambi RGBW	10 - Black 11 - White 12 - Silver 13 - Gold Bronze CU - Custom	- XXXX mm

Mounting

Recessed Trim (R)



Dimensions

