

Key Features


- Minimum bend radius is 300mm
- Easy diffuser installation
- Typical length is 2.5m (longer lengths available on request)
- Other RAL colours available on request
- Complete with mounting components
- Complies with relevant Australian standards
- Detailed shop drawings
- Even Illumination
- SELV LED Engine

Compliance



*Cyanosis compliant on request

Colour Options



Code

Example:

V3535RC-R109030ODD010-2400

Profile	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
V3535RC	R - Recessed	05 - 4.8W/m (270lm/m) 10 - 9.6 W/m (539lm/m) 15 - 14.4 W/m (808lm/m) 28 - 28.8W/m (1616lm/m)	80 - CRI>80 90 - CRI>90	30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K RGB3 - RGBW 3000K RGB4 - RGBW 4000K	OD - Opal	DO - Non-Dim DA - DALI-Dim SW - Switch-Dim CA - Casambi D4 - DALI RGBW C4 - Casambi RGBW	10 - Black 11 - White 12 - Silver 13 - Gold Bronze CU - Custom	- XXXX mm

Mounting

Recessed Trim (R)



Dimensions

