

MATRIX45-G

LED Downlight



Quick info

GENERAL

Recessed

Fixed

Round

LED

SMD LED module

3000K, 4000K

CRI>90

Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination

Beam angle 30°

PHYSICAL

Aluminium

Powder coating

Function


Designed with a minimalist aesthetic, this deep-recessed LED fixture features a sleek 45mm cutout and a soft, curved form.

Engineered for complete glare control and superior visual comfort, it offers a range of interchangeable beam angle lenses that are easily swapped without tools to suit various lighting needs.


Features

Spring clips for easy installation

Deep reflector to minimise glare



Dimensions



MATRIX45-G

LED Downlight

Ordering info

SYSTEM POWER

8W

COLOUR TEMPERATURE

3000K
4000K

COLOUR RENDERING INDEX

CRI>90

ELECTRICAL

Non-Dimmable

HOUSING

White
Black

LENS



30° Beam

Technical Information

Fitting	System LM	LED Wattage	System Wattage	CRI	Beam
MATRIX45-G-930-30	450lm	6W	8W	90	30°
MATRIX45-G-940-30	480lm	6W	8W	90	30°

Ordering Information

MATRIX45 - G - XXW - XX - XX - XX - ND - XX

Wattage	CRI	CCT	Lens	Controls	Finish
(6) 6W	(30) 3000K (40) 4000K	(90) CRI>90	(30) 30°	(ND) Non-Dim	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.