

# VEKTA VVB0715



## Key Features

- 50mm bend diameter
- Vertical Bending
- Solvent Resistant
- Dirt Resistant
- Remote 24V Driver
- Maximum length 10m (RGBW IS 8m)
- Other colours available on request
- Maximum length 10m (Mono, Tunable White, RGB)
- Maximum length 8m (RGBW)
- 100mm Cut length

## Compliance



## Code

Example:


VVB0715-S108022DED0-2400

Profile	Mounting	Power	CRI	CCT	Connector	Driver	Length
VVB0715	S - Surface Mount	10 - 10W/m (970lm/m)* 12 - 12W/M (408lm/m) (ONLY RGB) 15 - 15W/m (1329 lm/m)** (ONLY TW) 17 - 17W/m (758 lm/m)* (ONLY RGBW)	80 - CRI>80 90 - CRI>90***	22 - 2200K 27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K 65 - 6500K TW - Tunable White (2700K-5700K) RE - Red GR - Green BL - Blue RGB RGBW	DE - Direct SE - Side entry BE - Bottom JU - Jumper	DO - Non-Dim DA - Dali-Dim SW - Switch-Dim CA - Casambi	- XXXX mm


\* Based on CRI>80 and 4000K \*\*Based on CRI>80 \*\*\*MOQ on CRI>90

## Mounting


Surface Mounted (S)




## Flex Direction



## Mounting Channel



## Dimensions



\* Mounting Clip image is for reference and may change from strip to strip.