

MATRIX45-H

LED Downlight



Quick info

GENERAL

Recessed

Fixed

Round

LED

SMD LED module

3000K, 4000K

CRI>90

Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination

Beam angle 30°

PHYSICAL

Aluminium

Powder coating

Function

Designed with a minimalist aesthetic, this deep-recessed LED fixture features a sleek 45mm cutout and a soft, curved form.

Engineered for complete glare control and superior visual comfort, it offers a range of interchangeable beam angle lenses that are easily swapped without tools to suit various lighting needs.

Features


Spring clips for easy installation

Deep reflector to minimise glare



Decoration Reflector

Dimensions



MATRIX45-H

LED Downlight

Ordering info

SYSTEM POWER

8W

COLOUR TEMPERATURE

3000K
4000K

COLOUR RENDERING INDEX

CRI>90

ELECTRICAL

Non-Dimmable

HOUSING


White
Black

LENS



30° Beam

DECORATION RING



Silver



White



Gold



Black

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	Beam
MATRIX45-H-930-30	450lm	6W	8W	90	30°
MATRIX45-H-940-30	480lm	6W	8W	90	30°

Ordering Information

MATRIX45 - H - XXW - XX - XX - XX - XX - OF - XX

Wattage	CRI	CCT	Lens	Accessories	Controls	Finish
(6) 6W	(30) 3000K (40) 4000K	(90) CRI>90	(30) 30°	(SR) Secondary Silver Reflector (WR) Secondary White Reflector (GR) Secondary Gold Reflector (BR) Secondary Black Reflector	(ND) Non-Dim	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.