

# SMS-LED


LED SEALED SURFACE MOUNT TROFFER



## Key Features

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Heavy duty neoprene gasket ensures dust, insect and splash proof sealed for kitchens, hospitals, clean rooms and food preparation areas.
- Inverted diffuser in a screw fixed frame.
- Diffuser frame is connected to the body by safety lanyards.
- Suitable for fixing directly to ceiling or suspended with rods.
- Suitable for in-line mounting.
- High CRI available upon request.
- IP65 if surface mounted and sealed to the ceiling.

## Dimensions



## Technical Information

Configurations	Non Dim System wattage	Combined Board Output (lm)	Dimensions (mm)
1x08W	10.60	1220	612x300
2x08W	22.20	2440	612x300 & 1222x300
3x08W	28.76	3660	612x602
4x08W	38.10	4880	1222x300 & 1222x602
1x14W	17.62	2200	612x300
2x14W	34.34	4400	612x300 & 1222x300
3x14W	51.92	6600	612x602
4x14W	68.52	8800	1222x300 & 1222x602

## Code

SMS-LED/4X08/12X3/LO/40/ND

Product Series		# of boards		Wattage (W)		Nominal Dimensions (mm)		Diffuser		CCT		Driver		
SMS-LED	Surface Mount	1	1 Board	08	8W	6x3	600x300	LO	White Acrylic Microprism	30	3000K	ND	Non Dimming	
		2	2 Board	14	14W	6x6	600x600	MP		40	4000K	DALI	DALI Dimming	
		3	3 Board			12x3	1200x300						SD	Switch Dimming
		4	4 Board			12x6	1200x600							

Specifications subject to change without notice.