

OMBRE

VERSATILE LOW PROFILED TROFFER



OMBRE GRID LED



OMBRE AIR LED




OMBRE PLASTER LED

Key Features

- Robust construction metal powder coated body
- IP44 from below, IP30 from behind
- High performance microprism centre diffuser, secondary side diffusers & outer
- fine rib transition diffuser
- High efficiency & long life LED light source with matching control gear
- LED lumen maintenance at I90/B10 > 60,000 Hours
- Available in 3000K, Standard model is 4000K & Non-dimming
- CRI>80
- 3 Step MacAdam

Dimensions



*Nominal Dimensions shown **Check Coding table for variant lengths

Code

OMG1600L-D-3K

Product Series	Delivered Lumens	Wattage	Fitting Type	Nominal Dimensions			Cutout		Wiring Options			Colour Temp	
				Length	Width	Depth	Length	Width					
OMG16001L	1200	11	Recessed Grid	590	290	65	-	-	D EM ILD	DALI, DSI & SwitchDim Emergency Smart Luminaire Sensor	3K	3000K 4000K (Standard)	
OMG18501L	1387	13	Recessed Grid	590	290	65	-	-					
OMG32002L	2400	21	Recessed Grid	1190	290	65	-	-					
OMG37002L	2775	25	Recessed Grid	1190	290	65	-	-					
OMG41503L	3112	27	Recessed Grid	1490	290	65	-	-					
OMG48003L	3600	32	Recessed Grid	1490	290	65	-	-					
OMA16001L	1200	11	Recessed Air	590	290	65	-	-					
OMA18501L	1387	13	Recessed Air	590	290	65	-	-					
OMA32002L	2400	21	Recessed Air	1190	290	65	-	-					
OMA37002L	2775	25	Recessed Air	1190	290	65	-	-					
OMA41503L	3112	27	Recessed Air	1490	290	65	-	-					
OMA48003L	3600	32	Recessed Air	1490	290	65	-	-					
OMP16001L	1200	11	Recessed Plaster	635	335	65	605	305					
OMP18501L	1387	13	Recessed Plaster	635	335	65	605	305					
OMP32002L	2400	21	Recessed Plaster	1235	335	65	1205	305					
OMP37002L	2775	25	Recessed Plaster	1235	335	65	1205	305					

Specifications subject to change without notice.

