



Key Features

Optical Systems	White Acrylic Microprism	CCT	3000K 4000K
Mounting Type	Plaster Recessed Surface Mount Suspended T-Bar recessed	Colour Consistency (LED Module)	3 SDCM
Finish Options	White	COI Compliant	on request (<3.3 for 3500K and 4000K)
Warranty	5 Years	Lumen Output (Combined Board)	1220 - 8800lm
CRI	>80 >90 optional	Lifetime	L80 (B10) 70,000hrs

Application

Healthcare and commercial applications depending on specification.

Design

Manufactured in our Brisbane manufacturing facility, we control, test and construct to the highest standards, including materials used. OSIK has a robust construction process utilising 0.75 zincseal alloy, providing IP20 from above & below, utilising a high efficiency & long life LED light source, COI compliant on request. It also has a future-proof replacable gear tray, allowing for the technology to be upgraded at a later stage without updating the entire fitting. Available with Rod or Wire Suspensions (OSIK-S Only).

Installation

Plaster Recessed, Surface Mount, Suspended, T-Bar recessed (38mm Standard T-Bar) options. Also available with Rod or Wire Suspensions (OSIK-S Only).

Notes



- Data shown is standard, alternative options can be accomodated on request (1200x600 & 300x300).
- Data value may change depending on configurations and product availability.

Configurations


Configurations	Non Dim System wattage	Combined Board Output (lm)	Dimensions LxWxH (mm)
4x7.2W	33	4400	297x295x90
1x08W	10.6	1220	597x295x90
2x08W	22.2	2440	597x295x90 & 1200x295x90
3x08W	28.76	3660	597x590x90
4x08W	38.1	4880	1190x295x90 & 597x590x90
1x14W	17.62	2200	597x295x90
2x14W	34.34	4400	597x295x90 & 1190x295x90
3x14W	51.92	6600	597x590x90
4x14W	68.52	8800	1190x295x90 & 597x599x90

Specifications subject to change without notice.

Spectral Distribution & Photometrics



Dimensions



Cutout Dimensions	Fitting Dimensions
315x295	297x295
596x311	597x295
1196x311	1190x295
605x605	597x590

Code

OSIK-TB / 4X14 / 12X3 / LO / 40 / ND

Product Series		# of Boards		Wattage of Boards		Nominal Dimensions		Diffuser Type		CCT		Driver	
OSIK-TB OSIK-PB OSIK-S	T-bar	1	Board	07	7W	3x3	300x300	LO MP	White Acrylic Microprism	30	3000K	ND DALI SD	Non Dimming DALI Dimming Switch Dimming
	Plaster	2	2 Boards	08	8W	6x3	600x300			40	4000K		
	Surface Mount	3	3 Boards	14	14W	6x6	600x600						
		4	4 Boards			12x3	1200x300						