

LX26-RS40-24W

Round Spotlight Module



Quick info

GENERAL

Track Light

LED

COB LED module

3000K, 4000K

CRI>90

Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination

Beam angle 18°, 30°, 45°

PHYSICAL

Aluminium

Powder coating

Function


The LineX RS40 Spotlight module can be flexibly fixed and installed on the 48V magnetic track lighting system and widely applied for commercial and residential lighting environments.

Features



Dimensions

LX26-RS40-24W



LX26-RS40-24W

Round Spotlight Module

Ordering info

SYSTEM POWER
24W
COLOUR TEMPERATURE
3000K
4000K
COLOUR RENDERING INDEX
CRI>90

ELECTRICAL
Non-Dim

HOUSING
White
Black

LENS	
	
18° Beam	30° Beam
	
45° Beam	

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	CCT	Beam
LX26-RS40-12W-930	1500lm	22W	24W	90	3000K	18°
LX26-RS40-12W-940	1600lm	22W	24W	90	4000K	18°
LX26-RS40-12W-930	1500lm	22W	24W	90	3000K	30°
LX26-RS40-12W-940	1600lm	22W	24W	90	4000K	30°
LX26-RS40-12W-930	1200lm	22W	24W	90	3000K	45°
LX26-RS40-12W-940	1300lm	22W	24W	90	4000K	45°

Ordering Information

LX26 - RS40 - XXX - XX - XX - XX - ND - XX					
Wattage	CRI	CCT	Lens	Controls	Finish
(24) 24W	(30) 3000K (40) 4000K	(90) CRI>90	(18) 18° (30) 30° (45) 45°	(ND) Non-Dim	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.