

LX26-PS55-14W

Pendant Spotlight Module



Quick info

GENERAL

Track Light

LED

COB LED module

3000K, 4000K

CRI>90

Binning < 3-Step MacAdam

ESTIMATED LED LIFETIME

L80 / 50,000h

OPTICAL

Direct Illumination

Beam angle 18°, 24°, 36°

PHYSICAL

Aluminium

Powder coating

Function


The LineX PS55 Light Module can be flexibly fixed and installed on the 48V magnetic track lighting system and widely applied for commercial and residential lighting environments.

Features



Dimensions

LX26-PS55-14W



LX26-PS55-14W

Pendant Spotlight Module

Ordering info

SYSTEM POWER
14W

COLOUR TEMPERATURE
3000K
4000K

COLOUR RENDERING INDEX
CRI>90

ELECTRICAL
Non-Dim

HOUSING
White
Black

LENS



18° Beam



24° Beam



36° Beam

Technical Information

Fitting	Module Output	LED Wattage	System Wattage	CRI	CCT	Beam
LX26-PS55-14W-18-930	950Lm	13W	14W	90	3000K	18°
LX26-PS55-14W-18-940	1000Lm	13W	14W	90	4000K	18°
LX26-PS55-14W-24-930	950Lm	13W	14W	90	3000K	24°
LX26-PS55-14W-24-940	1000Lm	13W	14W	90	4000K	24°
LX26-PS55-14W-36-930	950Lm	13W	14W	90	3000K	36°
LX26-PS55-14W-36-940	1000Lm	13W	14W	90	4000K	36°

Ordering Information

LX26 - PS55 - XX - XX - XX - XX - ND - XX					
Wattage	CRI	CCT	Lens	Controls	Finish
(14) 14W	(30) 3000K (40) 4000K	(90) CRI>90	(18) 18° (24) 24° (36) 36°	(ND) Non-Dim	(10) Black (11) White

PLEASE REPLACE XX WITH THE FIGURE INSIDE THE BRACKETS LOCATED IN THE TABLE.