

RA-LED

RIGHT ANGLED REFLECTOR BATTEN



FEATURES

- Squareline batten range fabricated from 0.7mm Zincseal Steel with white powder coated finish.
- Steel reflector with white powder coated finish.
- Also available in 1.0mm Aluminium body for marine/corrosive environment.
- Suitable for fixing directly to ceiling or may be suspended with chains or rods.
- Ideal for blackboard/whiteboard lighting in teaching areas.
- Available in DALI Dim or Switch Dim.
- L80 B10.
- Rated 70,000 hours.
- Self Cooling LED Boards.
- Zhaga certified LED Boards.
- CRI>80.



CRI typically greater than



TECHNICAL INFORMATION

Contact Frend for other lighting configurations.

Number of Boards	Possible Configurations	Combined Board Output (lm)	Nominal Lengths (mm)
1	1x08W	1220 (lm)	600
2	2x08W	2440 (lm)	1200
1	1x14W	2200 (lm)	600
2	2x14W	4400 (lm)	1200

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	570 / 600 1170 / 1200
Width	85
Depth	137

PRODUCT CODE

Example code: RA-LED/2x08/12/40/ND

See Technical Information Table for configurations options
Specifications subject to change without notice

Product Series	Number of Boards	Wattage of Boards	Nominal Dimensions	LED Type	Driver
RA-LED Steel Body	1	08	6 600	30 3000K	ND Non Dim
RAAL-LED Aluminium Body	2	14	12 1200	40 4000K	DALI DALI Dim SD Switch Dim

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au