

# FHLP-LED

## LED DIFFUSED BATTEN



### FEATURES

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- Squareline batten range fabricated from 0.7mm zincseal steel with powder coated white finish.
- White ABS plastic end caps screw fixed to the fitting body.
- Formed with K12 prismatic diffuser.
- Wide body or narrow body available.
- Available in 1.0mm aluminium body for marine/corrosive environment (FHPAL-LED).
- Suitable for fixing directly to ceiling or may be suspended with chains or rods.
- DALI dim or switch dim available.



CRI typically greater than



### TECHNICAL INFORMATION

Contact Frend for other lighting configurations  
Refer to IES files for System Lumens

Configurations	Non Dim System Wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600/N
2x08W	22.20	2440	600/W & 1200/N
4x08W	38.10	4880	1200/W
1x14W	17.62	2200	600/N
2x14W	34.34	4400	600/W & 1200/N
4x14W	68.52	8800	1200/W

### SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	615 / 600
Width	71 - Narrow (N)
Depth	108

### PRODUCT CODE

Example code: FHLP-LED/2x08/12/N/40/ND

See Technical Information Table for configurations options.  
Specifications subject to change without notice.

Product Series	Number of Boards	Wattage of Boards	Nominal Dimensions	Fitting Width	Colour Temperature	Driver
FHLP-LED Steel Body	1	08	6 600	N Narrow	30 3000K	ND Non Dim
FHPAL-LED Aluminium Body	2	14	12 1200	W Wide	40 4000K	DALI DALI Dim
	4					SD Switch Dim