

PRYSM

LED SURFACE MOUNTED LOWBAY

FEATURES

- Square or round.
- IP65.
- CRI >80, CRI >90 available on request.
- L80 B20, >80 000 hrs @ tc = 85°C.
- Minimum colour tolerance: 3SDCM.
- IK08.
- UV stabilized polycarbonate diffuser.
- Non-dim or DALI.
- Suitable for undercover carparks, service corridors, internal and external walkways.



PRM-R



PRM-S

TECHNICAL INFORMATION

Contact Frend for other lighting configurations

Configurations	Wattage	LED Board Lumens (4000°K)
PRM-S	11	1905
PRM-S	16	2665
PRM-S	24	3610
PRM-R	13	2050
PRM-R	19	2965

SPECIFICATIONS

PRM-S	316 x 316 x 96mm
PRM-R	∅ 316 x 100mm

PRODUCT CODE

Example code: PRM-S/24/40/ND

See Technical Information Table for configurations options
Specifications subject to change without notice

Product Series	Wattage of Boards	LED Type	Driver
PRM-S Square	11 11W	30 3000K	ND Non Dim
	16 16W	40 4000K	DALI DALI Dim
	24 24W	50 5000K	
PRM-R Round	13 13W		
	19 19W		

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au