

FBLD

BALLAD - LED DIFFUSED BATTEN



FEATURES

- L70 B50.
- Rated 50,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- 7 year warranty.
- Batten range fabricated from 0.7mm zincseal steel with powder coated white finish.
- Dome diffuser.
- Suitable for fixing directly to ceiling or may be suspended with chains or rods.
- DALI dim or switch dim available.



7 Year Warranty



CRI typically greater than 80



TECHNICAL INFORMATION

Contact Frend for other lighting configurations

Configurations	Non Dim System Wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600
2x08W	22.20	2440	1200
1x14W	17.62	2200	600
2x14W	34.34	4400	1200

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	565.8 / 600
Width	30.7
Depth	62.8

PRODUCT CODE

Example code: FBLD/2x08/12/40/ND

See Technical Information Table for configurations options
Specifications subject to change without notice

Product Series	Number of Boards	Wattage of Boards	Nominal Length	Colour Temp.	Driver	
FBLD	Ballad	1	08	06 600	30 3000K	ND Non Dim
		2	14	12 1200	40 4000K	DALI DALI Dim
						SD Switch Dim

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au