

# ECB-LED

## ECONOBAY



### FEATURES

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- Rod or chain suspension or available in surface mount.
- Available in DALI dim or switch dim.
- High performance LED high bay.
- Low glare louvre.
- Air gap between body and luminaire open to improve life.



CRI typically greater than



### TECHNICAL INFORMATION

Contact Frend for other lighting configurations  
Refer to IES files for System Lumens

Configurations	Non Dim System Wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
4x08W	38.10	4880	1200x200
4x14W	68.52	8800	1200x200
8x08W	76.2	9760	1200x400
8x14W	137.04	17600	1200x400

### SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	1185 / 1200
Width	167 / 200 323 / 400
Depth	130

### PRODUCT CODE

Example code: ECB-LED/4x08/12x2/LVR/40/ND

See Technical Information Table for configurations options  
Specifications subject to change without notice

Product Series	Number of Boards	Wattage of Boards	Nominal Dimensions	Diffuser	Colour Temperature	Driver
ECB-LED Suspended	4	08	12x2 1200x200	LVR White directional low-glare louvre	30 3000K	ND Non Dim
ECB-LED-SM Surface	8	14	12x4 1200x400		40 4000K	DALI DALI Dim SD Switch Dim

**FREND**  
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

[www.frend.com.au](http://www.frend.com.au)