

# CWP-LED

## LED WEATHERPROOF



### FEATURES

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- IP65 weatherproof luminaire.
- IK07 impact resistant.
- Stainless steel toggle clip fixings.
- UV stabilized high impact polycarbonate diffuser.
- Available in DALI dim, switch dim or emergency.
- Tamper proof clips with self tapping screws available upon request.
- Stainless Steel spring fixing brackets for mounting onto surfaces.
- Suitable for suspension with the stainless steel triangle provided.
- Ambient temperature  $-25^{\circ}$  to  $45^{\circ}$



CRI typically greater than



### TECHNICAL INFORMATION

Contact Frend for other lighting configurations  
Refer to IES files for System Lumens

Configurations	Non Dim System Wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600
2x08W	22.20	2440	600 & 1200
4x08W	38.10	4880	1200
1x14W	17.62	2200	600
2x14W	34.34	4400	600 & 1200
4x14W	68.52	8800	1200

### SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	680 / 600 1292 / 1200
Width	110
Depth	86

### PRODUCT CODE

Example code: CWP-LED/4x08/12/40/TS/ND

See Technical Information Table for configurations options.  
Specifications subject to change without notice.

Product Series	Number of Boards	Wattage of Boards	Nominal Length	Colour Temperature	Tamper Proof Screws	Driver
CWP-LED	1	08	06 600	30 3000K	TS Tamper Proof Screws	ND Non Dim
	2	14	12 1200	40 4000K		DALI DALI Dim
	4					SD Switch Dim
						ME Emergency