

EDB

LED DIFFUSED BATTEN



FEATURES

- Built-in high efficiency SMD chips.
- Powder coated steel base.
- Highly transparent opal polycarbonate diffuser.
- Variable wattage, switch between 10/21W, 21/42W.
- Available in 4000K and 6500K.
- Large 6mm terminal block for easy installation.
- Quick install modular design.
- Non-maintained emergency option.
- CRA ≥ 80 .
- 50,000 hour lifetime.
- IP20 Rating.
- White Finish.
- L70B50
- Lumen Output:
 - 10/21W - 900/1900lm.
 - 21/42W - 1850/3800lm.

SPECIFICATIONS

Dimensions (mm)

| | |
|---------------|-----------------------------|
| Length | 600—10/21W 1200—21/42W |
| Width | 80 130 - Emergency 10/21 |
| Depth | 72 |

PRODUCT CODE

Example code: EDB/10/21/40/ND

Specifications subject to change without notice.

| Product Series | Wattage of Boards | Colour Temperature | Driver |
|----------------|------------------------|----------------------|----------------------------|
| EDB | 10/21 21W 21/42 42W | 40 4000K 65 6500K | ND Non Dim ME Emergency |

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au