

Why Choose 100100R

V100100R is a great option for recessed ceiling and wall lights. With an amplitude of colours and outputs there is an option to suit a wide range of architectural applications.

Compliance




*Cyanosis compliant on request

Key Features

- Dot free illumination
- Complies with relevant Australian Standards
- Diverse possibilities
- SELV LED Engine
- Emergency Options (On Request)
- Manufactured in Australia
- Up to 120 system lumens per system watt
- IP55 (On Request)

Colour Options



Code


Example:

V100100R-R129030ODD010-2400

Profile	Mounting	Power	CRI	CCT	Optics	Driver	Finish	Length
V100100R	R - Recessed	12 - 12 W/m	80 - CRI>80	30 - 3000K	OD - Opal	DO - Non-Dim	10 - Black	- XXXX mm
Optional	Trim	16 - 16 W/m	90 - CRI>90	35 - 3500K	AS - Asymmetric	DA - Dali-Dim	11 - White	
		20 - 20 W/m		40 - 4000K		SW - Switch-Dim	75 - Gray	
		24 - 24 W/m		50 - 5000K		CA - Casambi	79 - Anodised	
100100RIP		28 - 28 W/m		TW - 2700-6500K		T2 - Tunable White	CU - Custom	
		32 - 32 W/m						
		36 - 36 W/m						
		40 - 40 W/m						
		44 - 40 W/m						
		48 - 48 W/m						

Mounting

Recessed Trim (R)



Dimensions

