

FHL-LED

LED BATTEN



FEATURES

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- Squareline batten range fabricated from 0.7mm zincseal steel with powder coated white finish.
- Wide body or narrow body available.
- Available in 1.0mm aluminium body for marine/corrosive environment (FHLAL-LED).
- Suitable for fixing directly to ceiling or may be suspended with chains or rods.
- DALI dim or switch dim available.



CRI typically greater than



TECHNICAL INFORMATION

Contact Frend for other lighting configurations

Configurations	Non Dim System Wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600/N
2x08W	22.20	2440	600/W & 1200/N
4x08W	38.10	4880	1200/W
1x14W	17.62	2200	600/N
2x14W	34.34	4400	600/W & 1200/N
4x14W	68.52	8800	1200/W

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	615 / 600 1175 / 1200
Width	71 - Narrow 136 - Wide
Depth	108

PRODUCT CODE

Example code: FHL-LED/2x08/12/N/40/ND

See Technical Information Table for configurations options
Specifications subject to change without notice

Product Series	Number of Boards	Wattage of Boards	Nominal Dimensions	Fitting Width	Colour Temperature	Driver
FHL-LED Steel Body	1	08	6 600	N Narrow Body	30 3000K	ND Non Dim
FHLAL-LED Aluminium Body	2	14	12 1200	W Wide Body	40 4000K	DALI DALI Dim
	4					SD Switch Dim